

LK220

( )

LK220 -

Ethernet.

116

10 000.

10~125.

- 
- 
- 
- 
- 
- 
- 

Ethernet  
TCP/IP Modbus-TCP

SD-



1-1

LK220

- 10
  - 1
  - 
  - 
  - Ethernet.
- 1-1, :  
 (RUN, PRG, REM).  
 SD- /

PWR	r				
RUN		-			
ERR		-			
FRC		-			:
BAT					:
				90%	-
SDIN	SD-	-		SD-	
				/	SD-
				SD-	
LNK1				Ethernet 1	
	Ethernet 1			Ethernet 1	
ACT1				Ethernet 1	
	Ethernet 1			Ethernet 1	
LNK2		-		Ethernet 2	

	Ethernet 2			Ethernet 2	
ACT2			-	Ethernet 2	
	Ethernet 2			Ethernet 2	

Ethernet LK220 Ethernet. Ethernet STEP  
 RJ45 10/100 / ,  
 LK220  
 : RUN, PRG REM. REM  
 RUN, REM, PROG.

RUN		AutoThink.
REM		
PRG ( )		

RUN:

- 
- 
- 
- 
- 
- 

( )  
(Auto Think)

PRG ( ):

•  
•  
•  
•  
•  
•

( ).

REM: ( )

RUN REM,

RPG

REM,

REM

REM

) ( )  
)

•  
•  
•  
•  
•

IEC

IEC

PRG

IEC,

IEC

PRG.

LK220

LKA102

LKA 103.

1  
7

BAT

8.2.4

LK220	
	XC7Z015 667
	2,5 /
NOR-	32 (16 , 16 )
DDR	512 , 800 / , - 32
MRAM	512
SD-	32
Ethernet	
10/100M	2- TCP/IP
	: : : : : , BCD
	1 25°
PCI	
	2,5 / PCIE(1.0)
	4- x1
RS232	
	2- 115200 /
	IP20
	SD-
	10 000
( I)	128
( Q)	128
( G)	5
( M)	5
( R)	64
( S)	2
	19,4 ~28,8

LK220	
( . )	300 24 /
	≤40
( * * )	44,7 *166 *152
	0°C~60°C
	-40~70°C
	10%~95%,